

# 3GS8

## Sharp-Cutoff Twin Pentode With Common Cathode, Grid No.1, and Grid No.2

### 9-PIN MINIATURE TYPE

*The 3GS8 is the same as the 4GS8/4BU8 except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600. . . . .	3.15	volts

# 3HM5/3HA5

## High-Mu Triode

### 7-PIN MINIATURE TYPE

*The 3HM5/3HA5 is the same as the 6HM5/6HA5 except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.450 ± 0.030	amp
Voltage (AC or DC) at heater amperes = 0.450. . . . .	2.7	volts
Warm-up time (Average) . . . . .	11	sec

# 3HS8

## Sharp-Cutoff Twin Pentode

### 9-PIN MINIATURE TYPE

*The 3HS8 is the same as the 6HS8 except for the following items:*

#### Heater Characteristics and Ratings:

Current. . . . .	0.600 ± 0.040	amp
Voltage (AC or DC) at heater amperes = 0.600. . . . .	3.15	volts
Warm-up time (Average) . . . . .	11	sec

