

4BZ6

Semiremote-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BZ6 is the same as the 6BZ6 except for the following items:

Heater Characteristics and Ratings (*Design-Maximum Values*):

| | | |
|---|---------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater current = 0.450 | 4.2 | volts |
| Warm-up time (Average). | 11 | sec |

4BZ7

Medium-Mu Twin Triode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4BZ7 is the same as the 6BZ7 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

| | | |
|---|---------------|-------|
| Current | 0.600 ± 0.040 | amp |
| Voltage (AC or DC) at heater current = 0.600 | 4.2 | volts |
| Warm-up time (Average). | 11 | sec |

4CB6

Sharp-Cutoff Pentode

7-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

The 4CB6 is the same as the 6CB6 except for the following items:

Heater Characteristics and Ratings (*Design-Center Values*):

| | | |
|---|-----------------------|-------|
| Current | 0.450 ± 0.030 | amp |
| Voltage (AC or DC) at heater current = 0.450 | 4.2 | volts |
| Warm-up time (Average). | 11 | sec |
| Peak heater-cathode voltage: | | |
| Heater negative with respect to cathode. | 300 ^a max. | volts |
| Heater positive with respect to cathode. | 200 ^b max. | volts |

^a The dc component must not exceed 200 volts.

^b The dc component must not exceed 100 volts.

