

31C13

CATHODE RAY TUBE

Indirectly heated—for Radio DF Compass

TENTATIVE

GENERAL

The 31C13 is a magnetically focused and deflected cathode ray tube. The tube is aluminised, has a 6" diameter flat face, and is available with a "T1" screen which gives a green trace of medium persistence. It has an internal compass scale graduated with octantal correction and its face is treated to reduce specular reflection.

RATING

Heater Voltage	V_h	6.3	V
Heater Current	I_h	0.6	A
Maximum Anode Voltage	$V_{a(max)}$	10*	kV
Minimum Anode Voltage	$V_{a(min)}$	7.5	kV
Maximum Heater/Cathode Voltage d.c. (heater negative)	$V_{h-k(max)}$	150	V

* 10kV is a design centre rating. The absolute rating of 12.5kV maximum must not be exceeded.

INTER-ELECTRODE CAPACITANCES

Grid/All other electrodes	C_{g-all}	4.7	pF
Cathode/All other electrodes	C_{k-all}	5.3	pF

These capacitances include an Ediswan Clix wafer type duodecal holder.

TYPICAL OPERATION

Anode Voltage	V_a	9.5	kV
Grid Bias Voltage for cut-off of 140 mm focused line	V_g	-43 to -93	V
Average Peak to Peak Modulating Voltage for Modulation up to 150 μA		30	V
Maximum Peak to Peak Modulating Voltage for Modulation of limit Cathode Ray Tube up to 150 μA		35	V

A resistance should be inserted in the anode circuit in order to limit the discharge current to 100 mA(max), in the event of a flash-over inside the tube.

31C13

CATHODE RAY TUBE

Indirectly heated—for Radio DF Compass


TENTATIVE

DIMENSIONS

Maximum Overall Length	458	mm
Maximum Face Diameter	160	mm
Maximum Neck Diameter	35	mm
Approximate Nett Weight	2 $\frac{1}{2}$	lbs
Approximate Packed Weight	16 $\frac{1}{2}$	lbs

CAP—Cavity CT8

BASE—B12A (5 Pin)



Viewed from free end of pins

CONNECTIONS

Pin 1	Heater	h
Pin 2	Grid	g
Pin 3	No Pin	NP
Pin 4	No Pin	NP
Pin 5	No Pin	NP
Pin 6	No Pin	NP
Pin 7	No Pin	NP
Pin 8	No Pin	NP
Pin 9	No Pin	NP
Pin 10	No Connection	NC
Pin 11	Cathode	k
Pin 12	Heater	h
Cap	Anode	a