



OUTPUT TRIODE
 TRIODE DE SORTIE
 ENDTRIODE

Heating: indirect by A.C.;
 parallel supply
 Chauffage: indirect par C.A.; $V_f = 4$ V
 alimentation en parallèle $I_f = 1$ A
 Heizung: indirekt durch Wechselstrom;
 Parallelspeisung

Dimensions in mm
 Dimensions en mm
 Abmessungen in mm



Capacities
 Capacités
 Kapazitäten

$C_a = 3,2$ pF
 $C_g = 5,1$ pF
 $C_{ag} = 4$ pF

Typical characteristics
 Caractéristiques typiques
 Kenndaten

$V_a = 200$ V
 $V_g = -16$ V
 $I_a = 12$ mA
 $S = 1,3$ mA/V
 $\mu = 9$ -
 $R_i = 7$ k Ω
 $R_a = 27$ k Ω
 $V_i (I_g = +0,3 \mu A) = 10,5$ V_{eff}
 $W_o (I_g = +0,3 \mu A) = 0,22$ W

4614*"Miniwatt"*

Limiting values
Caractéristiques limites
Grenzdaten

V_{a_0}	= max.	400 V
V_a	= max.	200 V
W_a	= max.	3 W
I_k	= max.	30 mA
$V_g (I_g = +0,3 \mu A)$	= max.	-1,3 V
R_g	= max.	1 M Ω
V_{fk}	= max.	50 V
R_{fk}	= max.	20 k Ω

PHILIPS



*Electronic
Tube*

HANDBOOK

page	4614 sheet	date
1	1	1948.09.22
2	2	1948.09.22
3	FP	1999.06.07