

# 3AU6

## Sharp-Cutoff Pentode

### 7-PIN MINIATURE TYPE

*The 3AU6 is the same as the 6AU6A except for:*

#### Heater Characteristics and Ratings:

|                                                           |               |   |
|-----------------------------------------------------------|---------------|---|
| Current . . . . .                                         | 0.600 ± 0.040 | A |
| Voltage (AC or DC) at heater<br>amperes = 0.600 . . . . . | 3.15          | V |
| Warm-up time (Average) . . . . .                          | 11            | s |

# 3AV6

## Twin Diode—High-Mu Triode

### 7-PIN MINIATURE TYPE

*The 3AV6 is the same as the 6AV6 except for:*

#### Heater Characteristics and Ratings:

|                                                           |               |   |
|-----------------------------------------------------------|---------------|---|
| Current . . . . .                                         | 0.600 ± 0.040 | A |
| Voltage (AC or DC) at heater<br>amperes = 0.600 . . . . . | 3.15          | V |
| Warm-up time (Average) . . . . .                          | 11            | s |

# 3BA6

## Remote-Cutoff Pentode

*The 3BA6 is the same as the 6BA6 except for:*

#### Heater Characteristics and Ratings:

|                                         |               |   |
|-----------------------------------------|---------------|---|
| Current . . . . .                       | 0.600 ± 0.040 | A |
| Voltage (ac or dc) at 0.600 A . . . . . | 3.15          | V |
| Warm-up Time (Average). . . . .         | 11            | s |

# 3BN4A

## Medium-Mu Triode

*The 3BN4A is the same as the 6BN4A except for:*

#### Heater Characteristics and Ratings:

|                                         |               |   |
|-----------------------------------------|---------------|---|
| Current . . . . .                       | 0.450 ± 0.030 | A |
| Voltage (ac or dc) at 0.450 A . . . . . | 3             | V |
| Warm-up Time (Average). . . . .         | 11            | s |

# 3BN6

---

## Beam Tube

*The 3BN6 is the same as the 6BN6 except for:*

### Heater Characteristics and Ratings:

|                                         |                   |   |
|-----------------------------------------|-------------------|---|
| Current . . . . .                       | 0.600 $\pm$ 0.040 | A |
| Voltage (ac or dc) at 0.600 A . . . . . | 3.15              | V |
| Warm-up Time (Average). . . . .         | 11                | s |

# 3BU8/3GS8

---

## Sharp-Cutoff Twin Pentode

With Common Cathode

Grid No. 1, and Grid No. 2

*The 3BU8/3GS8 is the same as the 6BU8 except for:*

### Heater Characteristics and Ratings:

|                                         |                   |   |
|-----------------------------------------|-------------------|---|
| Current . . . . .                       | 0.600 $\pm$ 0.040 | A |
| Voltage (ac or dc) at 0.600 A . . . . . | 3.15              | V |
| Warm-up Time (Average). . . . .         | 11                | s |