



7112

7112

MAGNETRON

TUNABLE TYPE

FORCED-AIR COOLED

INTEGRAL MAGNET

*For use as a pulsed oscillator
at frequencies between 8500 and 9600 Mc*

The 7112 differs from the 7110 and the 7111 only mechanically in the location of the tuning control and the micrometer-type indicator provided to facilitate frequency calibration of each tube. The 7112 features a tuning shaft which permits the use of a remote control for adjustment. The 7112 is the same as the 7110 except for the following items:

Mechanical:


Tuning Shaft with Associated Calibrated Indicator:
Revolutions (Approx.) to cover full
range of 8500 to 9600 Mc 25

OPERATING CONSIDERATIONS

The 7112 can be tuned in the same manner as the 7110 except that a screw-driver slot is provided in the tuning shaft. If desired, a flexible coupling may be attached to this shaft and the tube tuned remotely. The design of the 7112 provides an essentially constant operating frequency without requiring a positive mechanical lock even though the tube is subjected to vibration.



MAGNETRON






7112

MAGNETRON

7112





7112

MAGNETRON

7112

REFERENCE PLANE A IS DEFINED AS THE PLANE THROUGH THAT PORTION OF THE MOUNTING FLANGE DESIGNATED AS ANNULAR SURFACE D.

REFERENCE PLANE B IS DEFINED AS THE PLANE WHICH IS PERPENDICULAR TO PLANE A AND PASSES THROUGH THE EXACT CENTERS OF MOUNTING-FLANGE HOLES 2 AND 3.

REFERENCE PLANE C IS DEFINED AS THE PLANE WHICH IS PERPENDICULAR TO PLANE A AND PLANE B AND PASSES THROUGH THE EXACT CENTERS OF MOUNTING-FLANGE HOLES 3 AND 4.

NOTE 1: SURFACE E OF THE WAVEGUIDE OUTPUT FLANGE AND THE ENTIRE SURFACE OF THE MOUNTING FLANGE ARE MADE SO THAT THEY MAY BE USED TO PROVIDE A HERMETIC SEAL.

NOTE 2: THE AXIS OF THE HEATER-CATHODE TERMINAL WILL BE WITHIN THE CONFINES OF A CYLINDER WHOSE RADIUS IS $3/64$ " AND WHOSE AXIS IS PERPENDICULAR TO REFERENCE PLANE A AT THE SPECIFIED LOCATION.

NOTE 3: ALL POINTS ON THE MOUNTING FLANGE WILL LIE WITHIN 0.015" ABOVE OR BELOW REFERENCE PLANE A.

NOTE 4: THE LIMITS INCLUDE ANGULAR AS WELL AS LATERAL DEVIATIONS.

NOTE 5: THESE DIMENSIONS DEFINE EXTREMITIES OF THE 0.169" INTERNAL DIAMETER OF THE CYLINDRICAL HEATER TERMINAL.

NOTE 6: THESE DIMENSIONS DEFINE EXTREMITIES OF THE 0.540" INTERNAL DIAMETER OF THE CYLINDRICAL HEATER-CATHODE TERMINAL.

NOTE 7: NO PART OF THE CONNECTOR DEVICE FOR THE HEATER AND HEATER-CATHODE TERMINALS SHOULD BEAR AGAINST THE UNDERSIDE OF THIS LIP.

NOTE 8: THE HEATER TERMINAL AND THE HEATER-CATHODE TERMINAL ARE CONCENTRIC WITHIN 0.010".

NOTE 9: ANODE TEMPERATURE MEASURED AT JUNCTION OF WAVEGUIDE AND ANODE BLOCK.

NOTE 10: CATHODE TEMPERATURE MEASURED HERE.