




DOUBLE TRIODE

6·3V INDIRECTLY HEATED

A1834

APRIL, 1953

BASE CONNECTIONS AND VALVE DIMENSIONS



View from underside
of base

Base : International octal
Bulb : Dome top pear

Overall length : 140 max. mm.
Seated length : 107 max. mm.
Diameter : 50 max. mm.

RATINGS

V_h	6·3	V
I_h	2·5	A
v_{h-k} (pk)	300 max.	V
Per system		
V_a	250 max.	V
P_a	13 max.	W
μ	2·1	
r_a	280	Ω
g_m	7·5	mA/V

} at V_a (b) = 135
 $I_a = 125$ mA

TYPICAL OPERATION

D.C. Amplifier (values per system)

	Max. rating	Typical operation	
V_a (b)	250	135	V
I_a	125	125	mA
P_a	13		W
R_k		250	Ω
$R_{g k}$		1	M Ω

Scanning Booster (Max. ratings per system)

PIV^*	1·7	kV
v_{h-k} (pk)	300	V
I_a	125	mA
P_a	13	W

* Duration of PIV limited to 10 μ s and should not exceed 15% of scanning cycle.

The maximum permissible D.C. resistance between grid and cathode is limited to 1 M Ω with auto-bias. Fixed bias operation is not recommended.

MOUNTING

Any position.

MARCONI'S WIRELESS TELEGRAPH COMPANY LIMITED

Head Office : Marconi House, Chelmsford · Telephone : Chelmsford 3221 · Telegraphic Address : Expense, Chelmsford
OV.2009

C.

Printed in England.

