

TUNG-SOL

GAS RECTIFIER

PHYSICAL SPECIFICATIONS

EMITTER IONICALLY HEATED		PIN CONNECTIONS	
BASE SMALL WAFER OCTAL 5-PIN		PIN 1 SHELL	PIN 7 FILAMENT
CAP ---		PIN 2 NONE	PIN 8 FILAMENT
BULB MT-8		PIN 3 STARTER ANODE	
MAX. DIAMETER 1 5/16"		PIN 4 NONE	MOUNTING POS. ANY
MAX. SEATED HEIGHT 2 1/16"		PIN 5 PLATE	
MAX. OVERALL LENGTH 2 5/8"		PIN 6 NONE	

THE OY4 IS A HALF-WAVE GAS RECTIFIER WITH A STARTER ANODE WHICH MAKES IT POSSIBLE TO OPERATE DIRECTLY FROM A 117-VOLT AC OR DC LINE.

RATINGS AND CHARACTERISTICS

HALF-WAVE RECTIFIER WITH CONDENSER INPUT TO FILTER
PINS 7 AND 8 MUST BE CONNECTED TOGETHER^A

MAXIMUM INVERSE PEAK VOLTAGE	300	VOLTS
MAXIMUM PEAK CURRENT	500	MA.
MAXIMUM DC OUTPUT CURRENT	75	MA.
MINIMUM DC OUTPUT CURRENT	40	MA.
MINIMUM SERIES ANODE RESISTANCE (117-VOLT LINE OPERATION)	50	OHMS
APPROXIMATE TUBE DROP	12	VOLTS
MAXIMUM DC STARTING VOLTAGE ^B	95	VOLTS

^A RAPID INTERMITTENT OPERATION IS UNDESIRABLE.

^B WITH STARTER ANODE CONNECTED TO THE ANODE THROUGH A 10 MEGOHM RESISTOR BY-PASSED WITH A 0.002 μF CONDENSER.

PRINTED IN U. S. A.

PLATE
1695
APRIL 15
1946