

# DISC SEAL TRIODE

# TD03-10F

*Indirectly heated disc seal triode, with internal feedback, primarily intended for use as a common grid earthed, anode, concentric line oscillator.*

This data should be read in conjunction with GENERAL OPERATIONAL RECOMMENDATIONS — TRANSMITTING VALVES included in this volume of the handbook.

## HEATER

$V_h$	6.3	V
$I_h$ (approx.)	400	mA

## MOUNTING POSITION

Any

## CAPACITANCES

$C_{a-g}$	1.4	pF
$C_{a-k}$	0.045	pF
$C_{g-k}$	1.7	pF

## CHARACTERISTICS (measured at $V_a = 250V$ , $I_a = 20mA$ , $V_g = -3.5V$ )

$g_m$	6.0	mA/V
$\mu$	30	

## COOLING

$T_{\text{anode seal max.}}$	140	°C
------------------------------	-----	----

In order to limit the anode seal temperature and also to limit the rate of change of anode seal temperature, it is necessary that the mass of metal in close thermal contact with the anode disc shall not be less than 60g (2oz) of brass or its thermal equivalent.

## LIMITING VALUES


$V_a$ max.	350	V
$p_a$ max.	10	W
$I_a$ max.	50	mA
$i_{a(pk)}$ max.	150	mA
$p_g$ max.	500	mW



# DISC SEAL TRIODE

# TD03-10F

Indirectly heated disc seal triode, with internal feedback, primarily intended for use as a common grid, earthed anode, concentric line oscillator.




ANODE CURRENT PLOTTED AGAINST ANODE VOLTAGE

# TD03-10F

## DISC SEAL TRIODE

*Indirectly heated disc seal triode, with internal feedback, primarily intended for use as a common grid, earthed anode concentric line oscillator.*



POWER OUTPUT PLOTTED AGAINST WAVELENGTH.