

Mullard

MEDIUM IMPEDANCE TRIODE

DA1

The DA1 is a medium impedance triode for use as a low frequency amplifier in compact equipment such as deaf aids.

FILAMENT CHARACTERISTICS

Filament Voltage 2.0 volts
Filament Current 0.05 amp

DIMENSIONS

Overall Length ...	= 60 mm.
Overall Diameter...	= 19 mm.

OPERATING DATA

Anode Voltage	$V_{aW} = 20$	40 volts
Anode Current	$I_{aW} = 100$	250 μA
Grid Voltage	$-V_{g1W} = 0.15$	0.25 volt
Slope	$S_W = 0.2$	0.4 mA/V
Internal Resistance	$R_{iW} = 150,000$	80,000 ohms
Amplification Factor	$G_W = 30$	32


CAPACITIES

Anode to Control Grid	$C_{ag1} = 1.6 \mu F$
Input	$C_{g1} = 3.8 \mu F$
Output	$C_a = 5.4 \mu F$

LIMITS

Maximum Anode Voltage	$V_{a_{max}} = 100$ volts
Maximum Resistance in Grid Circuit	$R_{g1f_{max}} = 1.0$ megohm
Range of Grid Voltage for 1 μA Grid Current at $V_a = 40$ V	$V_{g1} = 0$ to +1.0 volt

CONNECTIONS



- Pin No. 1 Anode
- „ 2 Grid
- „ 3 Filament
- „ 4 Filament

Viewed from free end of pins.

DA1

Mullard MEDIUM IMPEDANCE TRIODE

