

# RCA-8532

## HIGH-MU TRIODE

### "Premium" Version of 6J4

#### 7-PIN MINIATURE, FRAME-GRID TYPE

For Cathode-Drive UHF Amplifier Applications (up to 500 Mc/s) in Equipment Requiring Exceptional Stability and Reliability under Severe Environmental Conditions

Transconductance 11,000  $\mu$ mhos  
Amplification Factor 52.5

Can also be supplied to meet  
Military Specification MIL-E-1/1527(EL)

RCA-8532 is a high-mu triode of the 7-pin miniature type for cathode-drive-amplifier applications at frequencies up to 500 Mc/s. This "Premium" version of the 6J4 features frame-grid construction and Special Tests for long life and stability of characteristics in critical industrial applications under conditions of severe shock, vibration, and high altitude.



An internal shield connected to the grid reduces the cathode-to-plate capacitance, and thus minimizes undesirable feedback effects

when the tube is operated as a cathode-drive amplifier.

Three base-pin terminals are provided for the grid. At uhf frequencies, these terminals may all be connected to ground to minimize the effects of grid-lead inductance.

An RCA Dark Heater, rated at 6.3 volts/0.400 ampere, is utilized for long life and dependable performance.

The 8532 is unilaterally interchangeable with types 6J4, 6J4WA, and 6J4WB and may be used to replace these types in existing equipment.

For military applications, the 8532 can also be supplied to meet Military Specification MIL-E-1/1527 (EL) dated 24 February 1964, a copy of which may be obtained from: Specification Division, Naval Supply Depot, 5801 Tabor Avenue, Philadelphia, Pa. 19120.

#### GENERAL DATA

##### Electrical:

##### Heater Ratings and Characteristics:

Voltage (AC or DC) . . . . . 6.3  $\pm$  0.3 volts  
Current at 6.3 volts . . . . . 0.400 amp

##### Peak heater-cathode voltage:

Heater negative with respect to cathode . . . . . 100 max. volts  
Heater positive with respect to cathode . . . . . 100 max. volts

##### Direct Interelectrode Capacitances:<sup>a</sup>

Cathode to plate . . . . . 0.2 max. pf  
Input (Cathode-drive operation):  
K to (G + IS, H)<sup>b</sup> . . . . . 7.5 pf  
Output (Cathode-drive operation):  
P to (G + IS, H)<sup>b</sup> . . . . . 5.0 max. pf  
Grid and internal shield to plate . . . . . 2.8 pf  
Heater to cathode . . . . . 2.8 pf

##### Characteristics, Class A<sub>1</sub> Amplifier:

Plate Supply Voltage . . . . . 150 volts  
Grid . . . . . Connected to negative end of cathode resistor  
Cathode Resistor . . . . . 100 ohms  
Amplification Factor . . . . . 52.5  
Plate Resistance (Approx.) . . . . . 4800 ohms  
Transconductance . . . . . 11000  $\mu$ mhos  
Plate Current . . . . . 13.5 ma  
Grid Voltage (Approx.)  
for plate  $\mu$ a = 60 . . . . . -15 volts

##### Mechanical:

Operating Position . . . . . Any  
Type of Cathode . . . . . Coated Unipotential  
Maximum Overall Length . . . . . 2-1/8"  
Maximum Seated Length . . . . . 1-7/8"  
Maximum Diameter . . . . . 0.750"  
Dimensional Outline . . . . . JEDEC No. S-2  
Bulb . . . . . T5-1/2  
Base . . . . . Small-Button Miniature 7-Pin (JEDEC No. E7-1)

#### AMPLIFIER — Class A<sub>1</sub>

##### Maximum Ratings, Absolute-Maximum Values:

For operation at altitudes up to 80,000 feet and frequencies up to 500 Mc/s

Plate Voltage . . . . . 150 max. volts  
Grid Voltage:  
Negative-bias value . . . . . 55 max. volts  
Positive-bias value . . . . . 0 max. volts  
Cathode Current . . . . . 20 max. ma  
Plate Dissipation . . . . . 2.5 max. watts  
Bulb Temperature (At hottest point on bulb surface) . . . . . 120 max. °C

<sup>a</sup> With external shield JEDEC No. 316 connected to ground except as noted.

<sup>b</sup> With external shield JEDEC No. 316 connected to grid.



## Maximum Circuit Values:

## Grid-Circuit Resistance:

For grid-resistor-bias operation. 0.25 max. megohm

### CHARACTERISTICS RANGE VALUES FOR EQUIPMENT DESIGN

	Note	Min.	Max.	
Heater Current. . . . .	1	0.375	0.425	amp
Direct Interelectrode Capacitances:	2			
Cathode to plate. . . . .	3	-	0.2	pf
Input (Cathode-drive operation):				
K to (G + IS, H) . . . . .	4	5.5	9.5	pf
Output (Cathode-drive operation):				
P to (G + IS, H) . . . . .	4	-	5.0	pf
Grid and internal shield to plate. . . . .	3	2.3	3.3	pf
Heater to cathode . . . . .	3	1.0	4.5	pf
Plate Current (1) . . . . .	1,5	9	18	ma
Plate Current (2) . . . . .	1,6	-	60	μa
Transconductance (1). . . . .	1,5	8800	13200	μmhos
Transconductance (2) for an individual tube expressed as a per cent of Transconductance (1) . . . . .	5,7	-	15	%
Reverse Grid Current. . . . .	1,8	0	0.5	μa
Amplification Factor. . . . .	1,5	40	65	
Heater-Cathode Leakage Current:				
Heater negative with respect to cathode. . . . .	1,9	-	10	μa
Heater positive with respect to cathode. . . . .	1,9	-	10	μa
Leakage Resistance:				
Between grid and all other elements connected together . . . . .	1,10	500	-	megohms
Between plate and all other elements connected together . . . . .	1,11	500	-	megohms

Note 1: With ac or dc heater volts = 6.3.

Note 2: Measured in accordance with EIA Standard RS-191-A.

Note 3: With external shield JEDEC No.316 connected to ground.

Note 4: With external shield JEDEC No.316 connected to grid.

Note 5: With dc plate-supply volts = 150, grid connected to negative end of cathode resistor, cathode resistor (ohms) = 100, and cathode-bypass capacitor (μf) = 1000.

Note 6: With dc plate volts = 150 and dc grid volts = -15.

Note 7: With ac or dc heater volts = 5.7.

Note 8: With dc plate supply volts = 175, grid-circuit resistance (megohms) = 0.25, and cathode resistor (ohms) = 150.

Note 9: With dc heater-cathode volts = 100.

Note 10: With grid 100 volts negative with respect to all other elements connected together.

Note 11: With plate 300 volts negative with respect to all other elements connected together.

### SPECIAL TESTS

## High-Impact, Short-Duration Shock:

Peak Impact Acceleration. . . . .	450	g
Duration of half-sine-wave mechanical-shock pulse. . . . .	1	ms

This test is performed on sample tubes from each production lot to determine the ability of the tubes to withstand the specified acceleration for a short time interval. Tubes are rigidly mounted in each of four different positions (X<sub>1</sub>, X<sub>2</sub>, Y<sub>1</sub>, and Y<sub>2</sub>) in a Navy-Type High-Impact (Fly-weight) Shock Machine and, with heater volts = 6.3, dc plate supply volts = 150, dc grid volts = -1.5, grid resistor (megohms) = 0.1, dc heater-cathode volts = 100, are subjected to 20 blows (5 in each position) at a hammer angle of 30°.

Tubes are then criticized for changes in Transconductance (1), Reverse Grid Current, and Heater-Cathode Leakage Current under the conditions specified in the CHARACTERISTICS RANGE VALUES and are subjected to the Constant-Frequency Vibration Test and the Continuity and Shorts Test described below.

## Fatigue Vibration:

Peak Vibrational Acceleration . . . . .	5	g
Vibration Frequency, a constant value within the range of . . . . .	25 to 60	c/s
Duration of Test. . . . .	96	h

This test is performed on sample tubes from each production lot to determine the ability of the tubes to withstand the specified acceleration at a constant vibration frequency for an extended time interval. Tubes are rigidly mounted on a platform vibrating with simple harmonic motion at a constant vibration frequency within the range of 25 to 60 c/s and, with heater volts = 6.3, are subjected to the specified acceleration for 96 hours (32 hours in each of three different positions X<sub>1</sub>, X<sub>2</sub>, and Y<sub>1</sub>).

Tubes are then criticized for changes in Transconductance (1), Reverse Grid Current, and Heater-Cathode Leakage Current under the conditions specified in the CHARACTERISTICS RANGE VALUES and are subjected to the Constant-Frequency Vibration Test and the Continuity and Shorts Test described below.

## Constant-Frequency Vibration:

Peak Vibrational Acceleration . . . . .	10	g
Vibration Frequency : . . . . .	40	c/s
RMS Voltage across plate load resistor . . . . .	150 max.	mv

This test is performed on sample tubes from each production lot to determine if loose parts or mechanical resonance are present at the specified acceleration and vibration frequency. Tubes are rigidly mounted on a platform vibrating with simple harmonic motion at a constant frequency of

40 c/s and, with the tubes operating under the conditions specified in the CHARACTERISTICS RANGE VALUES for Transconductance (1) with the addition of a plate load resistor of 2000 ohms, are subjected to the specified acceleration. During this test, with a 60-c/s ac grid signal voltage, the rms voltage across the plate load resistor must not exceed 150 millivolts.

**Variable-Frequency Vibration:**

Peak Vibrational Acceleration . . . . .	10	g
Vibration-Frequency Range . . . . .	50 to 500	c/s
RMS Voltage across plate load resistor . . . . .	100 max.	mv

This test is performed periodically on sample tubes to determine if mechanical resonance is present at the specified acceleration over the specified frequency range. Tubes are rigidly mounted on a platform vibrating with simple harmonic motion over a frequency range of 50 to 500 c/s and, with the tubes operating under the conditions specified in the CHARACTERISTICS RANGE VALUES for Transconductance (1) with the addition of a plate load resistor of 2000 ohms, are subjected to the specified acceleration in each of two different positions,  $X_1$  and  $X_2$ . The acceleration over the frequency range is within  $\pm 20$  per cent of the reference acceleration at 100 c/s. The frequency is increased from 50 to 500 c/s with approximately logarithmic progression and 4 to 5 minutes are required to traverse the frequency range. During this test, with a 60-c/s ac grid signal voltage, the rms voltage across the plate load resistor must not exceed 100 millivolts.

**High-Altitude Voltage Breakdown:**

Effective Altitude. . . . .	80000	ft
Air Pressure. . . . .	$21 \pm 2$	mm Hg
Ambient Temperature . . . . .	$25 \pm 5$	$^{\circ}\text{C}$
RMS Voltage between plate base pin and adjacent pins. . . . .	500	volts

This test is performed on sample tubes from each production lot to determine the ability of the tubes to withstand high-altitude (low-air-pressure) conditions. In this test at an ambient temperature of  $25^{\circ} \pm 5^{\circ}\text{C}$ , while the tubes are subjected to a reduced air pressure of  $21 \pm 2$  mm Hg corresponding to an altitude of 80,000 feet, a 60-c/s, ac rms voltage of 500 volts is applied between the plate base pin and adjacent pins. Tubes must not break down (arc over) or show evidence of corona.

**Continuity and Shorts:**

This test is performed on sample tubes from

each production lot to determine the presence of open circuits, temporary or permanent shorts, or air leaks. Tubes are subjected to the Thyatron-Type Shorts Test described in Military Specification MIL-E-1D, Amendment 5, Paragraph 4.7.7.

**Heater-Cycling Life:**

Duration of Test. . . . . 2000 cycles

This test is performed on sample tubes from each production lot with heater volts = 7.0 cycled 1 minute ON and 4 minutes OFF for 2000 cycles, dc heater-cathode volts = 100 continuously ON, and no voltages applied to the plate or grid. After 2000 cycles, tubes are criticized for changes in Heater-Cathode Leakage Current and Leakage Resistance, and for Open Heaters, Open Cathode Circuits, and Heater-Cathode Shorts.

**Stability Life (20 Hours):**

This test is performed at room temperature on sample tubes from each production lot to determine if the tubes are properly stabilized. After 2 hours and again after 20 hours of operation under the conditions specified in the CHARACTERISTICS RANGE VALUES for Transconductance (1) with the addition of a grid resistor of 0.25 megohm and with dc heater-cathode volts = 100, tubes are criticized for the change in Transconductance (1).

**Early-Hour Survival-Rate Life (100 Hours):**


This test is performed on sample tubes from each production lot to assure a high early-hour survival rate. After 100 hours of operation under the conditions specified for the Stability Life Test above, tubes are criticized for the change in Transconductance (1) and are then subjected to the Continuity and Shorts Test.

**Intermittent-Conduction Life (1000 Hours):**

This test is performed on sample tubes from each production lot to assure the high quality of individual tubes and to guard against epidemic failures due to excessive changes in any of the characteristics specified below. After 500 hours of operation under the conditions specified for the Stability Life Test above and, in addition, with heater voltage cycled 110 minutes ON and 10 minutes OFF, and bulb temperature =  $120^{\circ}\text{C}$ , tubes are criticized for changes in Heater Current, Transconductance (1), Transconductance (2), Reverse Grid Current, Heater-Cathode Leakage Current, Leakage Resistance, and for Open Circuits, Permanent Shorts, Air Leaks, and Total Defectives. After 1000 hours of operation, tubes are again criticized for all of the preceding defects with the exception of the change in Transconductance (2).


Information furnished by RCA is believed to be accurate and reliable. However, no responsibility is assumed by RCA for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of RCA.

AVERAGE PLATE CHARACTERISTICS




92CM-12534

AVERAGE CHARACTERISTICS




92CM-12533

TERMINAL DIAGRAM  
Bottom View



- Pin 1 - Grid,  
Internal  
Shield
- Pin 2 - Cathode
- Pin 3 - Heater
- Pin 4 - Heater
- Pin 5 - Same as Pin 1
- Pin 6 - Same as Pin 1
- Pin 7 - Plate

DIMENSIONAL OUTLINE JEDEC No. 5-2  
Dimensions in Inches



\* Measured from base seat to bulb-top line as determined by a ring gauge of 7/16" inside diameter.  
\*\* The minimum applies in the zone starting 0.375" from the base seat.